



SAFETY DATA SHEET

Methanol SH HPLC grade

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Methanol SH HPLC grade
Product number	90018842
CAS number	67-56-1
EC number	200-659-6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	For research purposes only.
Uses advised against	No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier	Molekula Ltd. Lingfield Way, Darlington, DL1 4XX, United Kingdom +44 (0) 3302000333 info@molekula.com
----------	---

1.4. Emergency telephone number

+44 (0) 1380 725952

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

<u>Classification (EC 1272/2008)</u>	
Physical hazards	Flam. Liq. 2 - H225
Health hazards	Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370
Environmental hazards	Not Classified

2.2. Label elements

EC number	200-659-6
-----------	-----------

Hazard pictograms



Signal word

Danger

Methanol SH HPLC grade

Hazard statements	<p>H225 Highly flammable liquid and vapour.</p> <p>H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.</p> <p>H370 Causes damage to organs .</p>
Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P240 Ground and bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use non-sparking tools.</p> <p>P243 Take action to prevent static discharges.</p> <p>P260 Do not breathe vapour/ spray.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P308+P311 IF exposed or concerned: Call a POISON CENTER or doctor.</p> <p>P311 Call a POISON CENTER/ doctor.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P330 Rinse mouth.</p> <p>P361+P364 Take off immediately all contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.1. Substances

Product name	Methanol SH HPLC grade
CAS number	67-56-1
EC number	200-659-6
Chemical formula	CH ₄ O

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention. Place unconscious person on their side in the recovery position and ensure breathing can take place.

Methanol SH HPLC grade

Ingestion	Get medical attention immediately. Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Never give anything by mouth to an unconscious person. Place unconscious person on their side in the recovery position and ensure breathing can take place. Keep affected person under observation.
Skin contact	It is important to remove the substance from the skin immediately. Remove contamination with soap and water or recognised skin cleansing agent. Get medical attention.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse with water. Get medical attention if any discomfort continues.
Protection of first aiders	It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Drowsiness, dizziness, disorientation, vertigo. Unconsciousness. High concentrations may be fatal.
Ingestion	May cause stomach pain or vomiting. May cause severe internal injury.
Skin contact	A single exposure may cause the following adverse effects: Pain.
Eye contact	May be slightly irritating to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. Keep affected person under observation.
-----------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard. This product is toxic.
Hazardous combustion products	The product is flammable. Thermal decomposition or combustion products may include the following substances: Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Very toxic or corrosive gases or vapours. Use fire-extinguishing media suitable for the surrounding fire. Carbon dioxide (CO ₂). Carbon monoxide (CO).

5.3. Advice for firefighters

Methanol SH HPLC grade

Protective actions during firefighting	Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
Special protective equipment for firefighters	Wear chemical protective suit. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated. Avoid inhalation of vapours and spray/mists. Use suitable respiratory protection if ventilation is inadequate. Avoid contact with skin and eyes.
-----------------------------	--

6.2. Environmental precautions

Environmental precautions	Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Provide adequate ventilation. Absorb small quantities with paper towels and evaporate in a safe place. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. The contaminated absorbent may pose the same hazard as the spilled material. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.
--------------------------------	--

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.
------------------------------------	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Methanol SH HPLC grade

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. This product is toxic. Immediate first aid is imperative. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store away from incompatible materials (see Section 10). Store locked up. Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.

Storage class

Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

STEL

250ppm (333mg/m³) UK. EH40 WEL-Workplace exposure limits

TWA

200ppm (266mg/m³) UK. EH40 WEL-Workplace exposure limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Ensure the ventilation system is regularly maintained and tested. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.

Methanol SH HPLC grade

Respiratory protection	Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.
Environmental exposure controls	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Colourless.
Odour	Characteristic.
Odour threshold	10 ppm
pH	No information available.
Melting point	-98°C/-144.4°F
Initial boiling point and range	64.7°C/148.46°F
Flash point	9.7°C / 49.46°F Method: Closed cup.
Evaporation rate	6.3 (diethyl ether = 1)
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	Upper flammable/explosive limit: 44% (V) Lower flammable/explosive limit: 5.5%(V)
Vapour pressure	169.27 hPa @ 25°C/77°F
Vapour density	1.11
Relative density	0.791 g/ml at 25°C/77°F
Solubility(ies)	1000 g/l @ 20°C/68°F
Partition coefficient	log Pow: -0.77
Auto-ignition temperature	455.0°C/851°F
Decomposition Temperature	No information available.
Viscosity	kinematic:0.54-0.59 mm²/s @ 20°C/68°F dynamic: >0.544-<0.59 mPa s @ 25°C/77°F

9.2. Other information

Molecular weight	32.04
-------------------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Vapours may form explosive mixtures with air.
-------------------	---

10.2. Chemical stability

Methanol SH HPLC grade

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions A risk of explosion and/or of toxic gas formation exists with the following substances:

- Oxidising agents.
- perchloric acid
- perchlorates
- salts of oxyhalogenic acids
- chromium(VI) oxide
- halogens
- Oxides of nitrogen.
- nonmetallic oxides
- chromosulfuric acid
- chlorates
- Magnesium.
- Nitric acid (HNO₃).
- hydrogen peroxide
- sulfuric acid
- permanganic acid
- Exothermic reaction with:
- acid halides
- Strong reducing agents.
- Acids.
- Acid anhydrides.
- Bromine.
- chloroform
- Magnesium.
- Chlorine.
- Fluorine.
- Oxides of phosphorus.
- Risk of ignition or formation of inflammable gases or vapours with:
- Generates dangerous gases or fumes in contact with:
- Alkaline earth metals.
- Alkali metals.
- hydrides zinc diethyl

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented.

10.5. Incompatible materials

Materials to avoid Oxidising materials. Acids - oxidising. May attack some plastics, rubber and coatings.
Magnesium.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.
Carbon dioxide (CO₂).
Carbon monoxide (CO).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Methanol SH HPLC grade

Acute toxicity - oral

Summary Toxic if swallowed.

Acute toxicity oral (LD₅₀ mg/kg) 100.1

Species Rat

ATE oral (mg/kg) 100.1

Acute toxicity - dermal

Summary Toxic in contact with skin.

Acute toxicity dermal (LD₅₀ mg/kg) 300.1

Species Rabbit

ATE dermal (mg/kg) 300.1

Acute toxicity - inhalation

Summary Toxic if inhaled.

Acute toxicity inhalation (LC₅₀ vapours mg/l) 3.1

Species Rat

ATE inhalation (vapours mg/l) 3.1

Skin corrosion/irritation

Summary Based on available data the classification criteria are not met.

Serious eye damage/irritation

Summary Based on available data the classification criteria are not met.

Respiratory sensitisation

Summary Based on available data the classification criteria are not met.

Skin sensitisation

Summary Based on available data the classification criteria are not met.

Germ cell mutagenicity

Summary Based on available data the classification criteria are not met.

Carcinogenicity

Summary Based on available data the classification criteria are not met.

IARC carcinogenicity None of the ingredients are listed or exempt.

Reproductive toxicity

Summary Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

Summary Causes damage to organs .

Specific target organ toxicity - repeated exposure

Summary Based on available data the classification criteria are not met.

Aspiration hazard

Summary Based on available data the classification criteria are not met.

Methanol SH HPLC grade

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Drowsiness, dizziness, disorientation, vertigo. Unconsciousness. High concentrations may be fatal.
Ingestion	May cause stomach pain or vomiting. May cause severe internal injury.
Skin contact	A single exposure may cause the following adverse effects: Pain.
Eye contact	May be slightly irritating to eyes.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target organs	No specific target organs known.

SECTION 12: Ecological information

Ecotoxicity	Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.
--------------------	---

12.1. Toxicity

Acute aquatic toxicity

Summary	Based on available data the classification criteria are not met.
----------------	--

Chronic aquatic toxicity

Summary	Based on available data the classification criteria are not met.
----------------	--

12.2. Persistence and degradability

Persistence and degradability	The degradability of the product is not known.
--------------------------------------	--

12.3. Bioaccumulative potential

Bioaccumulative potential	No data available on bioaccumulation.
----------------------------------	---------------------------------------

Partition coefficient	log Pow: -0.77
------------------------------	----------------

12.4. Mobility in soil

Mobility	No data available.
-----------------	--------------------

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

Other adverse effects	None known.
------------------------------	-------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
Disposal methods	Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

Methanol SH HPLC grade

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1230
UN No. (IMDG)	1230
UN No. (ICAO)	1230
UN No. (ADN)	1230

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	METHANOL
Proper shipping name (IMDG)	METHANOL
Proper shipping name (ICAO)	METHANOL
Proper shipping name (ADN)	METHANOL

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID subsidiary risk	6.1
ADR/RID classification code	FT1
ADR/RID label	3
IMDG class	3
IMDG subsidiary risk	6.1
ICAO class/division	3
ICAO subsidiary risk	6.1
ADN class	3
ADN subsidiary risk	6.1

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ICAO packing group	II
ADN packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS	F-E, S-D
-----	----------

Methanol SH HPLC grade

ADR transport category	2
Emergency Action Code	•2WE
Hazard Identification Number (ADR/RID)	336
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Health and Safety at Work etc. Act 1974 (as amended). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. EH40/2005 Workplace exposure limits.
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways. RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail. IATA: International Air Transport Association. ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air. IMDG: International Maritime Dangerous Goods. CAS: Chemical Abstracts Service. ATE: Acute Toxicity Estimate. LC ₅₀ : Lethal Concentration to 50 % of a test population. LD ₅₀ : Lethal Dose to 50% of a test population (Median Lethal Dose). EC ₅₀ : 50% of maximal Effective Concentration. PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.
--	--

Methanol SH HPLC grade

Classification abbreviations and acronyms	Flam. Liq. = Flammable liquid Acute Tox. = Acute toxicity STOT SE = Specific target organ toxicity-single exposure
Classification procedures according to Regulation (EC) 1272/2008	Acute Tox. 3 - H311: Acute Tox. 3 - H331: Acute Tox. 3 - H301: STOT SE 1 - H370: : Expert judgement. Flam. Liq. 2 - H225: : Expert judgement.
Training advice	Only trained personnel should use this material.
Revision date	28/10/2021
Revision	1
SDS number	423
Hazard statements in full	H225 Highly flammable liquid and vapour. H301 Toxic if swallowed. H311 Toxic in contact with skin. H331 Toxic if inhaled. H370 Causes damage to organs .

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.